



Tattoo, the small revolution

Latest birth from Evolis product range, the **Tattoo** printer is a mixture of technology and innovation. Hi-Tech Design, compactness and ease of use, the **Tattoo** revolutionizes the world of monochrome printing on plastic cards.

Within seconds, the **Tattoo** personalizes in monochrome your pre-printed or blank plastic cards. It prints your high resolution text, bar codes, graphics and logos.



Compact, yet elegant

The **Tattoo** melts perfectly into your environment. It owes its extreme compactness to the Lift Card system which allows the passage of cards on two levels. A completely new system, designed by the Evolis R&D department.

Autonomous, it can also function without a computer, simply connected to a keyboard. Enter your data (name, number, bar code, encoding) and print your cards completely independently. This innovative design is ideal for point of sale and exhibition receptions.

Easy to use, yet powerful

Innovating, the **Tattoo** is equipped with an ingenious process of detachable card feeders. A technology allowing several series of cards to be prepared at the same time. A solution all the more revolutionary since an automatic gauge system analyses the thickness of the cards during each card feeder change. Completely enclosed, the card feeder is dust proof and thus guarantees an optimal card printing quality.

Astute, the **Tattoo** offers a double operating mode simultaneously: Card by card manual feeding from the front mouth and automatic feeding with the 100-cards feeder from the back.

Ergonomic, its opening system allows a direct access to the inside of the printer and thus makes the installation of consumables very easy and quick. The print head can be replaced in a few seconds by the operator without any tool or adjustment thanks to its Push & Twist concept.

Hi-Tech, yet economic

Its price positioning and its cost per printed card make the **Tattoo** the best quality / price ratio on the market of monochrome plastic card printers.





Evolis Tattoo Specifications

Printing mode >	■ Monochrome Thermal Transfer in Line Mode or Diffusion Mode for photo printing		
Printer specification >	■ Integrated Ribbon Saver		
Printing speed >	■ 500 cards/hour		
Resolution >	■ 300 dpi (11.8 dots/mm)		
Windows™ drivers >	■ For Windows™ 95 / 98 / Me / NT 4.0 / 2000 and Xp		
Warranty >	■ Printer: 1 year ■ Print Head: 1 year, unlimited number of prints ¹		
Ribbons type >	■ Mono Color Ribbon: 600 cards/roll ■ Colors available: black, blue, red, green, white, gold, silver, scratch off		
Card loading modes >	■ Manual feeding and/or automatic feeding		
Options >	■ USB port (cable supplied) ■ Serial port ■ Additional interchangeable card feeder		
Other printer models >	<table border="0"> <tr> <td>■ Tattoo Mag Printer with HICO/LOCO magnetic stripe encoder - ISO 7811</td> <td>■ Tattoo Stand-Alone Printer connected to a keyboard, available upon study</td> </tr> </table>	■ Tattoo Mag Printer with HICO/LOCO magnetic stripe encoder - ISO 7811	■ Tattoo Stand-Alone Printer connected to a keyboard, available upon study
■ Tattoo Mag Printer with HICO/LOCO magnetic stripe encoder - ISO 7811	■ Tattoo Stand-Alone Printer connected to a keyboard, available upon study		



1 - Clause governing the use of Evolis consumables



[Loyalty cards]



[Pass cards]



[Loyalty cards]



[Visitor badges]



[Business cards]



[Season cards]

Other specifications

- | | |
|--|--|
| ■ Programming Language ePL | ■ Printer weight:
2,5 kg (5.5lbs) |
| ■ Card types:
All PVC and Composite Polyester | ■ Communication interface:
Centronics Parallel (cable supplied) |
| ■ Card format:
ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm) | ■ Electrical:
110-230 Volts CA, 60-50 Hertz |
| ■ Card thickness:
from 0,25 mm (10 mil) to 0.76 mm (30 mil) | ■ Environmental: |
| ■ Card feeder capacity:
100 cards (0,76 mm-30 mil) - 300 cards (0,25 mm-10 mil) | - Min / Max operating temperatures: 15°C / 30°C |
| ■ Printer size: | - Humidity: 20% to 65% non-condensing |
| - Height: 166 mm (6.53") | - Min / Max storage temperatures: -5°C / +70°C |
| - Width: 290 mm (11.42") | - Storage humidity: 20% to 70% non-condensing |
| - Depth: 187 mm (7.36") | - Operating ventilation: free air. |

Headquarters:
Evolis Card Printer
29 avenue de la Fontaine
Z.I. Angers Beaucouzé
49070 BEAUCOUZÉ - France
Tel: +33 (0) 241 367 606
Fax: +33 (0) 241 367 612
info@evolis.com
www.evolis.com

Evolis Asia / Pacific
151 - D King's Road, #17-14
SINGAPORE 268161
Singapore
Tel: +65 4745901
Fax: +65 4765771

